

Technical Datasheet

Create Date: 03.01.2018 - Seite 1/1

Adhesive Spray



universal use

Adhesive Spray can be used universally and bonds light materials to themselves and among each other.

Adhesive Spray is suitable for the bonding of numerous materials such as paper, cardboard, pasteboard, wood, thin veneers, cork, leather, textiles, felt, soft foam, rubber, foam rubber, and plastic film (except for PVC and polyethylene). It is especially suited for the bonding of hard foam (e.g. polystyrene).

Technical Data

Base	synthetic rubber
Processing temperature	+10 to +30 °C
Evaporation time	5 - 15 min.
Open time max.	30 min.
Effectiveness	4 m ²
Temperature resistance	-20 to +65 °C
Storage stability	12 months

Processing

1. Shake can before use. Surfaces must be dry, clean and free of grease. Spray on one surface at about 15 to 30 cm distance. With porous materials, Adhesive Spray should be applied on both surfaces.

2. Depending on surface characteristics and ambient temperature, let the spray dry (approx. 10 minutes) until the adhesive is no longer stringy.

3. Position the parts and join them with strong pressure.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE
 Tel: +971 6 5262004 • Fax: +971 6 5262030
 info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1
 60327 Frankfurt/Main, Germany
 Tel: +49 (0) 69 710456072