

Anti-Spatter Spray



SLV-tested silicone-free

Anti-Spatter Spray contains no silicone and is used to clean welding nozzles and to keep them clean. At the same time, it protects the work piece to be welded against the effect of weld splashes without impairing the welding seam.

Anti-Spatter Spray prevents the adhesion of welding splashes on gas nozzles and workpiece surfaces, offers gap-free protection for the welding process, and makes follow-up cleaning of the workpieces with a spatula, brush or chisel superfluous.

Post-treatment of the work-piece such as: bronzing, galvanisation, anodising or painting is possible without special cleaning.

Technical Data

Odour	solvent
Features	SLV-tested, silicone-free
Storage stability	24 months
Colour	colourless

Processing

Spray on welding nozzles at a distance of about 15 cm. To protect the work piece surface, hold can at about 25 cm distance and spray on an area of approx. 10 cm to the left and right of the weld seam. Start welding process in hollow parts and narrow spaces only after evaporation of the propellant.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE
 Tel: +971 6 5262004 • Fax: +971 6 5262030
 info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1
 60327 Frankfurt/Main, Germany
 Tel: +49 (0) 69 710456072