

# Mould Release Agent Spray



## silicone-free sliding and release agent

Mould Release Agent Spray is a silicone-free sliding and release agent. The high-grade combination of active ingredients, consisting of pure natural products, has a high sliding effect which prevents its adhesion to plastics, moulds, metals and tools.

Mould Release Agent Spray can be used in plastic processing and for spraying, pressing, and vacuum deforming.

### Technical Data

Odour	solvent
Features	silicone-free
Storage stability	24 months
Colour	colourless
Temperature resistance	-20 to +130 °C

### Processing

Surfaces must be dry, clean and free of grease (use Cleaner Spray S). Shake can and spray at about 25 cm from surface. The special valve allows working in any position.

### Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

### Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

## Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE  
 Tel: +971 6 5262004 • Fax: +971 6 5262030  
 info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1  
 60327 Frankfurt/Main, Germany  
 Tel: +49 (0) 69 710456072